



Rectifieuses planes - Ziersch - ZT 24 - MACH-ID 9344



Rectifieuses planes - Ziersch - ZT 24

MACH-ID 9344

Marque Ziersch

Taper ZT 24

Année 2010

Contrôle Mitsubishi TOUCH Panel



Caractéristiques

X - Courses	600 inch
Y - Courses	220 inch
Z - Courses	540 inch
Table Length	400 inch
Table Width	250 inch
Charge sur table	250
Feed rate X-Axis	30000 mm/min.
Feed rate Z-Axis	30000 mm/min.
Meule dimensions	250 x 38 x 50,8 inch

Dimensions

Longueur	120.079 inch
Largeur	80.709 inch
Hauteur	98.819 inch

Important : les informations sur cette page ont été obtenues au meilleur de nos connaissances auprès des fabricants. L'exactitude n'est pas garantie mais les informations sont données de bonne foi. En conséquence, cela ne constitue pas une représentation ou des conditions contractuelles. Nous vous recommandons de vérifier tous les détails essentiels !



Transito 21
6909 DA Babberich
51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal



Rectifieuses planes - Ziersch - ZT 24 - MACH-ID 9344



- Sturdy, cast iron execution of all machine components
- High machine weight for maximum rigidity
- Preloaded precision linear guideways in the vertical- and cross axis (Bosch Rexroth) for highest accuracy
- Scraped and turcite coated slideways in the longitudinal axis provide excellent vibration absorption and a high-quality grinding surface pattern.
- Hydraulic longitudinal motion with return cooling unit to achieve good surfaces
- Electro-mechanic cross- and vertical motion
- Measuring systems in vertical axis (Heidenhain) for precise positioning
- Maintenance-free paper band filtration unit with up to 500 l tank and 2-bar pressure pump for effective cooling and rinsing
- Integrated rinsing channel
- Magnetic separator for prefiltration of the paper band filtration unit
- Infinitely variable grinding spindle motor
- Machine lamp
- Table-mounted dressing device for high precision and surface finish
- Electro-permanent magnetic chuck (SAV) with integrated pole changing unit and traction regulation
- Partial encapsulation of the machine with sliding door and a service door
- Effective splash guard and an excellent accessibility
- Preparation of the machine for installation of a coolant mist exhaust unit

Control system features:

- Very comfortable and easy to operate Z-control
- Automatic vertical infeed with dressing amount compensation
- Fully automatic grinding cycle with dressing cycles
- Easy operation via touchscreen
- Large and clear colour screen (10.4")
- Electronic handwheel, usable in vertical- and cross axis

Important : les informations sur cette page ont été obtenues au meilleur de nos connaissances auprès des fabricants. L'exactitude n'est pas garantie mais les informations sont données de bonne foi. En conséquence, cela ne constitue pas une représentation ou des conditions contractuelles. Nous vous recommandons de vérifier tous les détails essentiels !



Transito 21
 6909 DA Babberich
 51.9066195, 6.14990950

T: +31 (0)316 247 123
 F: +31 (0)316 247 123
 W: www.mach4metal.com

E: info@mach4metal.com
 E: sales@mach4metal.com
 E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
 t twitter.com/mach4metal

