



Vlakslijpmachines - Ziersch - ZT 24 - MACH-ID 9344



Vlakslijpmachines - Ziersch - ZT 24

MACH-ID 9344

Merk Ziersch

Type ZT 24

Bouwjaar 2010

Besturing Mitsubishi TOUCH Panel



Specificaties

Verplaatsing X - as	600 mm
Verplaatsing Y - as	220 mm
Verplaatsing Z - as	540 mm
Tafellengte	400 mm
Tafelbreedte	250 mm
Tafelbelasting	250
Voeding X-as	30000 mm/min.
Voeding Z-as	30000 mm/min.
Slijpsteen afmeting	250 x 38 x 50,8 mm

Afmetingen

Lengte	3050 mm
Breedte	2050 mm
Hoogte	2510 mm

Belangrijk: De informatie op deze pagina is naar beste vermogen en overtuiging verkregen en waar nodig verkregen van de fabrikanten. De nauwkeurigheid kan niet worden gegarandeerd maar de informatie wordt te goeder trouw gegeven. Dienovereenkomstig vormt het geen vertegenwoordiging of contractuele voorwaarden. We raden u aan om alle essentiële details te controleren!



Transito 21
6909 DA Babberich
51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal





Vlakslijpmachines - Ziersch - ZT 24 - MACH-ID 9344



- Sturdy, cast iron execution of all machine components
- High machine weight for maximum rigidity
- Preloaded precision linear guideways in the vertical- and cross axis (Bosch Rexroth) for highest accuracy
- Scraped and turcite coated slideways in the longitudinal axis provide excellent vibration absorption and a high-quality grinding surface pattern.
- Hydraulic longitudinal motion with return cooling unit to achieve good surfaces
- Electro-mechanic cross- and vertical motion
- Measuring systems in vertical axis (Heidenhain) for precise positioning
- Maintenance-free paper band filtration unit with up to 500 l tank and 2-bar pressure pump for effective cooling and rinsing
- Integrated rinsing channel
- Magnetic separator for prefiltration of the paper band filtration unit
- Infinitely variable grinding spindle motor
- Machine lamp
- Table-mounted dressing device for high precision and surface finish
- Electro-permanent magnetic chuck (SAV) with integrated pole changing unit and traction regulation
- Partial encapsulation of the machine with sliding door and a service door
- Effective splash guard and an excellent accessibility
- Preparation of the machine for installation of a coolant mist exhaust unit

Control system features:

- Very comfortable and easy to operate Z-control
- Automatic vertical infeed with dressing amount compensation
- Fully automatic grinding cycle with dressing cycles
- Easy operation via touchscreen
- Large and clear colour screen (10.4")
- Electronic handwheel, usable in vertical- and cross axis

Belangrijk: De informatie op deze pagina is naar beste vermogen en overtuiging verkregen en waar nodig verkregen van de fabrikanten. De nauwkeurigheid kan niet worden gegarandeerd maar de informatie wordt te goeder trouw gegeven. Dienovereenkomstig vormt het geen vertegenwoordiging of contractuele voorwaarden. We raden u aan om alle essentiële details te controleren!



Transito 21
6909 DA Babberich
51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal

