



Плоскошлифовальные станки - Ziersch - ZT 24 - MACH-ID 9344



Плоскошлифовальные станки - Ziersch - ZT 24

MACH-ID 9344

Производитель Ziersch

Тип ZT 24

Год выпуска 2010

Контроль Mitsubishi TOUCH Panel



Спецификации

Х ось	600 mm
У ось	220 mm
Z ось	540 mm
Длина стола	400 mm
Ширина стола	250 mm
Нагрузка на стол	250
Скорость подачи Х ось	30000 mm/min.
Скорость подачи Z ось	30000 mm/min.
Размеры шлифовального камня	250 x 38 x 50,8 mm

Размеры

Длина	3050 mm
Ширина	2050 mm
Высота	2510 mm

Обратите внимание: Информация на странице была получена по мере наших возможностей от производителей, где это возможно. Она размещена добросовестно, но ее точность не может быть гарантирована. Соответственно, это не является показателем или договорными условием. Мы советуем уточнить все спецификации!



Transito 21
6909 DA Babberich
51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal



Плоскошлифовальные станки - Ziersch - ZT 24 - MACH-ID 9344



- Sturdy, cast iron execution of all machine components
- High machine weight for maximum rigidity
- Preloaded precision linear guideways in the vertical- and cross axis (Bosch Rexroth) for highest accuracy
- Scraped and turcite coated slideways in the longitudinal axis provide excellent vibration absorption and a high-quality grinding surface pattern.
- Hydraulic longitudinal motion with return cooling unit to achieve good surfaces
- Electro-mechanic cross- and vertical motion
- Measuring systems in vertical axis (Heidenhain) for precise positioning
- Maintenance-free paper band filtration unit with up to 500 l tank and 2-bar pressure pump for effective cooling and rinsing
- Integrated rinsing channel
- Magnetic separator for prefiltration of the paper band filtration unit
- Infinitely variable grinding spindle motor
- Machine lamp
- Table-mounted dressing device for high precision and surface finish
- Electro-permanent magnetic chuck (SAV) with integrated pole changing unit and traction regulation
- Partial encapsulation of the machine with sliding door and a service door
- Effective splash guard and an excellent accessibility
- Preparation of the machine for installation of a coolant mist exhaust unit

Control system features:

- Very comfortable and easy to operate Z-control
- Automatic vertical infeed with dressing amount compensation
- Fully automatic grinding cycle with dressing cycles
- Easy operation via touchscreen
- Large and clear colour screen (10.4")
- Electronic handwheel, usable in vertical- and cross axis

Обратите внимание: Информация на странице была получена по мере наших возможностей от производителей, где это возможно. Она размещена добросовестно, но ее точность не может быть гарантирована. Соответственно, это не является показателем или договорными условиями. Мы советуем уточнить все спецификации!



Transito 21
 6909 DA Babberich
 51.9066195, 6.14990950

T: +31 (0)316 247 123
 F: +31 (0)316 247 123
 W: www.mach4metal.com

E: info@mach4metal.com
 E: sales@mach4metal.com
 E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
 t twitter.com/mach4metal

