



Плоскошліфувальні верстати - Ziersch - ZT 24 - MACH-ID 9344



Плоскошліфувальні верстати - Ziersch - ZT 24

MACH-ID 9344

Виробник Ziersch

Тип ZT 24

Рік випуску 2010

КОНТРОЛЬ Mitsubishi TOUCH Panel



Технічні характеристики

Х - Подорож	600 mm
Y-Travel	220 mm
Z - Подорож	540 mm
Довжина столу	400 mm
Ширина таблиці	250 mm
Навантаження на стіл	250
Швидкість подачі по осі Х	30000 mm/min.
Швидкість подачі по осі Z	30000 mm/min.
Розміри точильного каменю	250 x 38 x 50,8 mm

Розміри

Довжина	3050 mm
Ширина	2050 mm
Висота	2510 mm

Будь ласка, зверніть увагу: інформація на цій сторінці було отримано в міру наших можливостей і переконань, а також, де це можливо, від виробників. Він надається сумлінно, але його точність не може бути гарантована. Відповідно, це не буде представництвом або договірними умовами. Радимо перевіряти всі важливі деталі!



Transito 21
6909 DA Babberich
51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal



Плоскошліфувальні верстати - Ziersch - ZT 24 - MACH-ID 9344



- Sturdy, cast iron execution of all machine components
- High machine weight for maximum rigidity
- Preloaded precision linear guideways in the vertical- and cross axis (Bosch Rexroth) for highest accuracy
- Scraped and turcite coated slideways in the longitudinal axis provide excellent vibration absorption and a high-quality grinding surface pattern.
- Hydraulic longitudinal motion with return cooling unit to achieve good surfaces
- Electro-mechanic cross- and vertical motion
- Measuring systems in vertical axis (Heidenhain) for precise positioning
- Maintenance-free paper band filtration unit with up to 500 l tank and 2-bar pressure pump for effective cooling and rinsing
- Integrated rinsing channel
- Magnetic separator for prefiltration of the paper band filtration unit
- Infinitely variable grinding spindle motor
- Machine lamp
- Table-mounted dressing device for high precision and surface finish
- Electro-permanent magnetic chuck (SAV) with integrated pole changing unit and traction regulation
- Partial encapsulation of the machine with sliding door and a service door
- Effective splash guard and an excellent accessibility
- Preparation of the machine for installation of a coolant mist exhaust unit

Control system features:

- Very comfortable and easy to operate Z-control
- Automatic vertical infeed with dressing amount compensation
- Fully automatic grinding cycle with dressing cycles
- Easy operation via touchscreen
- Large and clear colour screen (10.4")
- Electronic handwheel, usable in vertical- and cross axis

Будь ласка, зверніть увагу: інформацію на цій сторінці було отримано в міру наших можливостей і переконань, а також, де це можливо, від виробників. Він надається сумлінно, але його точність не може бути гарантована. Відповідно, це не буде представництвом або договірними умовами. Радимо перевіряти всі важливі деталі!



Transito 21
 6909 DA Babberich
 51.9066195, 6.14990950

T: +31 (0)316 247 123
 F: +31 (0)316 247 123
 W: www.mach4metal.com

E: info@mach4metal.com
 E: sales@mach4metal.com
 E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
 t twitter.com/mach4metal

