

Multi-tasking lathes - MAZAK - INTEGREX 200-4 S - MACH-ID 9810



Multi-tasking lathes - MAZAK - INTEGREX 200-4 S

MACH-ID 9810

Make MAZAK
Type INTEGREX 200-4 S
YOP 2010
Control MAZATROL MATRIX



Specifications

Max. turning Ø	660 mm
Y-Axis	160 mm
Z-Axis	1045 mm
Spindle bore	82 mm
Speedrange	5000 Rpm
X-Axis	580 mm
B Axis	225 °
Spindle power	18.5 kW
Subspindle speeds	6000 Rpm

Dimensions

Length	4500 mm
Width	2400 mm
Height	2900 mm
Weight	9200 kg

Please Note: The information on this page has been obtained to the best of our ability and belief, and from the manufacturers where possible. It is given in good faith, but its accuracy can not be guaranteed. Accordingly, it will not form a representation or constitute contractual terms. We advise you to check any vital details!



Transito 21
 6909 DA Babberich
 51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal





Multi-tasking lathes - MAZAK - INTEGREX 200-4 S - MACH-ID 9810



The **Mazak INTEGREX 200-IV S** is a **multi-tasking CNC turning and milling center with a second/sub-spindle**. The “S” indicates the **sub-spindle**, allowing complete machining of both sides of a workpiece in a single setup.

Typical specifications include a **maximum machining diameter of approximately 660 mm**, a **machining length of around 995 mm**, and X/Y/Z travels of approximately **580 / 160 / 1,045 mm**. The machine features a **B-axis milling head**, a main spindle and sub-spindle up to approximately **5,000 rpm**, and a milling spindle typically capable of **12,000 rpm**. It normally uses **Capto C6 tooling** and is often equipped with a **40-position automatic tool changer**.

Machines manufactured around **2006–2010** are commonly equipped with the **Mazatrol Matrix CNC control**.

The INTEGREX 200-IV S is designed for **complete machining of complex components**, combining turning, milling, drilling, tapping and 5-axis positioning in one machine. This significantly reduces the number of setups and eliminates the need to move components between separate turning and milling machines.

Please Note: The information on this page has been obtained to the best of our ability and belief, and from the manufacturers where possible. It is given in good faith, but its accuracy can not be guaranteed. Accordingly, it will not form a representation or constitute contractual terms. We advise you to check any vital details!



Transito 21
6909 DA Babberich
51.9066195, 6.14990950

T: +31 (0)316 247 123
F: +31 (0)316 247 123
W: www.mach4metal.com

E: info@mach4metal.com
E: sales@mach4metal.com
E: buy@mach4metal.com

f www.facebook.com/Mach4Metal/
t twitter.com/mach4metal

